	nited S	[11]	Patent Number:			4,798,876		
Gould et al.			[45]	Date	of	Patent:	Jan. 17, 1989	
[54]	HYDROP COMPOSI	4,279,795 7/1981 Yamashita et al						
[75]	Inventors:	Francis E. Gould; Ellen K. Morgan, both of Princeton; Stephen D. Reduker, Somerset, all of N.J.	FOREIGN PATENT DOCUMENTS					
			41-9 252	040 5/19 638 12/19	66 85	Japan Japan	525/458 525/458	
[73]	Assignee:	Tyndale Plains-Hunter Ltd., Princeton, N.J.	Primary Examiner—John F. Terapane Assistant Examiner—John S. Maples Attorney, Agent, or Firm—Ratner & Prestia					
[21]	Appl. No.:	797,407						
[22]	Filed:	Nov. 12, 1985	[57]			ABSTRACT		
[51] [52]				Water absorptive polyurethane composition, having high mechanical strength, is formed of A. about 25% to about 75% of a hydrophilic polyether polyurethane which is the reaction product of diethylene glycol and a polyoxyethylene glycol having a molecular weight of about 1000 to about 8000 with a polyisocyanate and B. about 75% to about 25% of a hydrophobic polyester				
[58]								
[56]	References Cited							
	U.S. I	polyurethane which is the reaction product of a poly- functional polyester derived from the condensation of a						
3	3,876,581 4/1	974 Kyle et al	polyol wi	th a poly	r d bas	erived from the acid with a	ne condensation of a polyisocyanate.	
3	3,961,629 6/1	976 Richter et al 604/369		7 (Clai	ms, No Draw	ings	